


MYSLOT®-IV
NK-03 Series

Inverter-controlled **TABLE SPOT WELDER**

NK-03H100-15-K-EZ



[SPECIFICATIONS]

TRANSFORMER	: Inverter
RATED CAPACITY	: 40kVA AC380 ~ 480V 1Φ 50/60Hz
GUN TYPE	: HORIZONTAL
MAXIMUM CURRENT	: 12000Amp
AIR PRESSURE	: 0.6Mpa
ELECTRODE FORCE	: 2.5kN
GUN LENGTH	: 690mm
DUTY CYCLE	: 7%
TABLE SIZE	: 115x1000x1500mm
TABLE HEIGHT	: 700mm(FIXED)
COOLING WATER	: 8.5L/min or more
ELECTRODE TIP	: φ13 or φ16 (TAPA1/10)
COOLING UNIT	: EQUIPPED
MACHINE SIZE	: W1925×D1985×H2535mm
WEIGHT	: 1450Kg


Reference of Welding Capacity :

Mild Steel (2.3×2.3mm) Galvanized (2.3×2.3mm)
Stainless (2.5×2.5mm) Galvanized (2.3×2.3mm)

*Above mentioned materials are slightly different by manufacturer, or by country in the process of production. KOYO GIKEN INC. warrants the performance of our product MYSLOT, not warrants those materials and its thickness.


MADE IN JAPAN

P.Nr. EP2749373(CE), P.Nr. US9202622(US), P.Nr. ZL201310021859.6(CH)
P.Nr. AU2012371845(AUS), P.Nr. KR101417791(KR), P.Nr. TWI509645(TW)



MYSLOT® reaches deep location of weld points!

You can weld NUTS too!



NEW TIMER ~QUICK AND EASY TO SET.

EasySetting
EasyTimer



Reference parameter appears by only selecting material and thickness.

Pressure setting and water flow check automatically.
Tip dress counter equipped.

Anti-Oxidation System for Stainless Steel



Produces cleaner welds with no burn marks on the finish side of stainless assemblies.

KOYO GIKEN INC.

2-7-6 Hashimotodai Midori-ku Sagami-hara-City Kanagawa-Pref. 252-0132
TEL +81-42-770-4306 FAX +81-42-770-4310 E-MAIL info-hp@koyogiken.co.jp

03-1E 2012.01.01_K005-00-049

koyo giken
www.koyogiken.co.jp